ZB系列 MOQ:500

PICTURE 图片																			
MODLE 型号	ZB 8X30	ZB 8X30C	ZB 7X50	ZBZ 7X50	ZBZ 7X50C	ZBZB 7X50C	ZBZC 7X50C	ZBZ3 7X50	ZBZ3 7X50C	ZBZA 7X50C	ZBZA 7X50	ZBZA 10X60	ZBZA 20X80	ZBZA 20X100	ZBZB 7X50C	ZBW 8X42C	ZBG 8X42C	ZB 8X30C	ZBT 8X42C
MAGNIFICATION 倍数	8X	8X	7X	7X	7X	7X	7X	7X	7X	7X	7X	10X	20X	25X	7X	8X	8X	8X	8X
OVERLOOK DIAMETER 目镜直径	18	18	24	23	23	23	23	24	24	24	24	24	24	34	24	23	23	18	23
OVERCAPS SYSTEM 盖帽系统				Flip the blindfold	Flip the blindfold			Flip the blindfold	Flip the blindfold							Screw up	Screw up		Screw up
OBJECTIVE DIAMETER(MM) 物镜直径	30	30	50	50	50	50	50	50	50	50	50	60	80	100	50	42	42	30	42
FRONT LENS DIAMETER(MM) 前镜直径	45	45	64	61	61	61	61	64	64	64	64	80	102	115	64	48	48	45	48
PRISM 棱镜系统	BAK4	BAK4	BAK4	BAK4	BAK4	BAK4	BAK4	BAK4	BAK4	BAK4	BAK4	BAK4	BAK4	BAK4	BAK4	BAK4	BAK4	BAK4	BAK4
FOCUS SYSTEM 调焦系统	PORRO	PORRO	PORRO	PORRO	PORRO	PORRO	PORRO	PORRO	PORRO	PORRO	PORRO	PORRO	PORRO	PORRO	PORRO	ROOF	ROOF	PORRO	ROOF
LENS COATING 镜片镀膜	FMC	FMC	FMC	FMC	FMC	FMC	FMC	FMC	FMC	FMC	FMC	FMC	FMC	FMC	FMC	FMC	FMC	FMC	FMC
EXIT PUPIL DIAMETER 出瞳直径	3.75	3.75	7.1	7	7	7.1	7.1	7.1	7.1	7.1	7.1	6	4	4	7.1	4.2	4.2	3.75	4.2
EYE RELIEF 出瞳距离	16	16	23	24	34	24	24	23	23	23	24	20	18	20	23	23	23	16	23
FIELD OF VIEW 视场	8 °	8 °	7.5°	7 °	7 °	7 °	7°	7.5°	7.5°	7.5°	7.5°	5.5°	4°	3°	7.5°	7°	7°	8 °	7°
	在/1,000Yds	439ft/1000Yds	439ft/1000Yds	429ft/1000Yds	400ft/1000Yds	400ft/1000Yds	400ft/1000Yds	400ft/1000Yds	429ft/1000Yds	429ft/1000Yds	439ft/1000Yds	438ft/1000Yds	314ft/1000Yds	226ft/1000Yds	115ft/1000Yds	429ft/1000Yds	400ft/1000Yds	400ft/1000Yds	400ft/1000Yds
	米/1,000M	140M/1000M	140M/1000M	131M/1000M	122M/1000M	122M/1000M	122M/1000M	122M/1000M	131M/1000M	131M/1000M	131M/1000M	131M/1000M	96M/1000M	69M/1000M	34M/1000M	131M/1000M	122M/1000M	122M/1000M	122M/1000M
CLOSE DISTANCE(M) 近焦距	3	3	3	4	4	4	4	3	3	4	4	10	15	50	3	3	3	3	3
RELATIVE BRIGHTNESS 亮度系数	14	14	50.4	50	50	50.4	50.4	50.4	50.4	50.4	50.4	36	16	16	50.4	17.6	17.6	14	17.6
TWILIGHT INDEX 暗视指数	15.5	15.5	18.7	19	19	18.7	18.7	18.7	18.7	18.7	18.7	24.5	40	50	18.7	18.3	18.3	15.5	18.3
DIOPTER ADJUSTMENT 屈光调节	±5	±5	±4	±5	±5	±5	±5	±5	±4	±4	±5	±5	±4	±4	±4	±4	±4	±5	±4
WATER PROOF 防水	YES/IPX7	YES/IPX7	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES/IPX7	YES/IPX7	YES/IPX7	YES/IPX7	YES	YES	YES/IPX7	YES
NITROGEN FILLED 氮气充电	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
DIMENSIONS OF PRODUCT 产品尺寸	145x75x115	145x75x115	200X123X150	205X70X147	205X70X147	205X70X147	205X70X147	205X123X150	205X123X150	205X123X150	205X123X150	195X	258X	365X	205X123X150	130X47X47	130X47X47	145x75x115	130X47X47
NET WEIGHT(G) 产品重量	575	595	1360	1020	1050	1120	1120	1150	1360	1360	1360	2220X2202X79	320X102X340	388X246X115	1360	450	450	595	450
								长宽高					长宽高						
PICKING 包装	10pcs / Carton ; 10kg/ Carton ; Carton size: 556x42x203 mm	10pcs / Carton ; 10kg/ Carton ; Carton size: 556x42x203 mm	8pcs / Carton ; 16kg/ Carton ; Carton size: 575x530x245mm	10pcs / Carton ; 15kg/ Carton ; Carton size: 555x505x210mm	10pcs / Carton ; 13kg/ Carton ; Carton size: 555x505x210mm	10pcs / Carton ; 15kg/ Carton ; Carton size: 575x470x218mm	10pcs / Carton ; 13kg/ Carton ; Carton size: 575x470x218mm	10pcs / Carton ; 20.5kg/ Carton ; Carton size: 605x503x207mm	10pcs / Carton ; 20.5kg/ Carton ; Carton size: 605x503x207mm									

DB系列 MOQ:500

PICTURE 图片								
MODLE 型号	DW 8X42	DW 7X50	DWZ 8X40	DWZ 7X50	DW-B 7X50	DW-B 7X35	DW-B 7X50	DW-B 10X50
MAGNIFICATION 倍数	8X	7X	8X	7X	7X	7X	7X	10X
OVERLOOK DIAMETER 目镜直径	23	23	17	23	18	23	23	23
OVERCAPS SYSTEM 盖帽系统								
OBJECTIVE DIAMETER(MM) 物镜直径	35	50	40	50	50	35	50	50
FRONT LENS DIAMETER(MM) 前镜直径	42	64	42	64	46	44	64	74
PRISM 棱镜系统	BK7	BK7	BK7	BK7	BK7	BK7	BAK4	BAK4
FOCUS SYSTEM 调焦系统	PORRO	PORRO	PORRO	PORRO	PORRO	PORRO	PORRO	PORRO
LENS COATING 镜片镀膜	MC	MC	MC	MC	MC	MC	FMC	FMC
EXIT PUPIL DIAMETER 出瞳直径	5.2	7.1	4	7.1	5	7.1	7.1	7
EYE RELIEF 出瞳距离	16	16	16	16	16	16	23	23
FIELD OF VIEW 视场	7.5°	7°	7.5°	7.5°	7°	7°	7°	4°
	在/1,000Yds	429ft/1000Yds	400ft/1000Yds	429ft/1000Yds	429ft/1000Yds	651ft/1000Yds	439ft/1000Yds	344ft/1000Yds
	米/1,000M	131M/1000M	122M/1000M	131M/1000M	131M/1000M	198M/1000M	140M/1000M	105M/1000M
CLOSE DISTANCE(M) 近焦距	3	3	3	3	3	3	3	3
RELATIVE BRIGHTNESS 亮度系数	27	50.4	25	50.4	50.4	25	50.4	25
TWILIGHT INDEX 暗视指数	18.3	18.7	17.8	18.7	18.7	11.8	18.7	24.5
DIOPTER ADJUSTMENT 屈光调节	±4	±4	±4	±4	±4	±4	±4	±4
WATER PROOF 防水	YES	YES	YES	YES	YES	YES	YES	YES
NITROGEN FILLED 氮气充电	NO	NO	NO	NO	NO	NO	YES	YES
DIMENSIONS OF PRODUCT 产品尺寸	180X140X57	191X150X65	187X142X52	191X150X62	195X138X64	195X138X54	180X143X120	198X165X52
NET WEIGHT(G) 产品重量	680	760	700	935	970	730	950	1150
PICKING 包装								

DY系列 MOQ:500

PICTURE 图片									
MODLE 型号	DY1 8X42	DY1 10X42	DY2 8X42	DY2 10X42	DY3 8X42	DY3 10X42	DYT 8X42	DYT 10X42	DYT 12X42
MAGNIFICATION 倍数	8X	10X	8X	10X	8X	10X	8X	10X	12X
OVERLOOK DIAMETER 目镜直径	22	22	22	22	22	22	22	22	22
OVERCAPS SYSTEM 盖帽系统	Screw up	Screw up	Screw up	Screw up	Screw up	Screw up	Screw up	Screw up	Screw up
OBJECTIVE DIAMETER(MM) 物镜直径	42	42	42	42	42	42	42	42	42
FRONT LENS DIAMETER(MM) 前镜直径	52	52	52	52	52	52	52	52	52
PRISM 棱镜系统	BAK4	BAK4	BAK4	BAK4	BAK4	BAK4	BK7	BK7	BK7
FOCUS SYSTEM 调焦系统	ROOF	ROOF	ROOF	ROOF	ROOF	ROOF	ROOF	ROOF	ROOF
LENS COATING 镜片镀膜	FMC	FMC	FMC	FMC	FMC	FMC	FMC	FMC	FMC
EXIT PUPIL DIAMETER 出瞳直径	5.2	4.2	5.2	4.2	5.2	4.2	5.2	4.2	3.5
EYE RELIEF 出瞳距离	15.5	15.5	15.5	15.5	15.5	15.5	17.2	15.2	13
FIELD OF VIEW 视场	6.46°	6.12°	6.46°	6.12°	6.46°	6.12°	6.17°	5.8°	4.57°
	在/1,000Yds	113ft/1000Yds	113ft/1000Yds	113ft/1000Yds	113ft/1000Yds	113ft/1000Yds	113ft/1000Yds	113ft/1000Yds	87ft/1000Yds
	米/1,000M	37M/1000M	37M/1000M	37M/1000M	37M/1000M	37M/1000M	37M/1000M	37M/1000M	26M/1000M
CLOSE DISTANCE(M) 近焦距	2	2	2	2	2	2	2	2	2
RELATIVE BRIGHTNESS 亮度系数	27	17.6	27	17.6	27	17.6	27	17.6	12.3
TWILIGHT INDEX 暗视指数	18.3	22.5	18.3	22.5	18.3	22.5	18.3	20.5	22.5
DIOPTER ADJUSTMENT 屈光调节	±4	±4	±4	±4	±4	±4	±5	±5	±5
WATER PROOF 防水	YES	YES	YES	YES	YES	YES	YES	YES	YES
NITROGEN FILLED 氮气充电	YES	YES	YES	YES	YES	YES	YES	YES	YES
DIMENSIONS OF PRODUCT 产品尺寸	150x52x127	150x52x127	150x52x127	150x52x127	150x52x127	150x52x127	135x56x140	135x56x158	135x56x158
NET WEIGHT(G) 产品重量	410	410	410	410	410	410	713	753	753
PICKING 包装									

RU系列 MOQ:500

PICTURE 图片				
MODLE 型号	RU 8X32	RU 10X40	RU 12X45	RU 15X50
MAGNIFICATION 倍数	8X	10X	12X	15X
OVERLOOK DIAMETER 目镜直径	20	20	20	20
OVERCAPS SYSTEM 盖帽系统				
OBJECTIVE DIAMETER(MM) 物镜直径	32	40	50	50
FRONT LENS DIAMETER(MM) 前镜直径	42	47	60	67
PRISM 棱镜系统	N-K5L	N-K5L	N-K5L	N-K5L
FOCUS SYSTEM 调焦系统	PORRO	PORRO	PORRO	PORRO
LENS COATING 镜片镀膜	FMC	FMC	FMC	FMC
EXIT PUPIL DIAMETER 出瞳直径	4	4	4.2	4
EYE RELIEF 出瞳距离	17.5	17.5	17.5	17.5
FIELD OF VIEW 视场	7.5°	7.5°	7°	6.5°
	在/1,000Yds	426ft/1000Yds	400ft/1000Yds	375ft/1000Yds
	米/1,000M	131M/1000M	122M/1000M	113M/1000M
CLOSE DISTANCE(M) 近焦距	3	3	3	3
RELATIVE BRIGHTNESS 亮度系数	16.4	16	17.6	10
TWILIGHT INDEX 暗视指数	15.5	20.5	24.5	30
DIOPTER ADJUSTMENT 屈光调节	±5	±5	±5	±5
WATER PROOF 防水	NO	NO	NO	NO
NITROGEN FILLED 氮气充电	NO	NO	NO	NO
DIMENSIONS OF PRODUCT 产品尺寸	145X52X125	170X56X150	180X62X150	205X60X170
NET WEIGHT(G) 产品重量	575	650	750	720
PICKING 包装				

YP系列 MOQ:500

PICTRUE	图片					
MODLE	型号	TB 7X32	TB 7X35	TB 8X40	TB 10X50	TB 15X60
MAGNIFICATION	倍数	7X	8X	10	15	15X
EYEPIECE DIAMETER	目镜直径	32	20	28	35	20
EYEGLASS SYSTEM	目镜结构					
OBJECTIVE DIAMETER(MM)	物镜直径(MM)	32	35	40	50	60
FRONT LENS DIAMETER(MM)	前镜直径(MM)	45	42	47	60	67
PRISM	棱镜	BK7	BK7	BK7	BK7	BK7
FOCUS SYSTEM	调焦结构	PORRO	PORRO	PORRO	PORRO	PORRO
LENS COATING	镜片镀膜	MC	FMC	FMC	FMC	FMC
EXIT PUPIL DIAMETER	出瞳直径	4.6	5	3	5	4
EYE RELIEF	出瞳距离	23	17.5	17.5	17.5	17.5
FIELD OF VIEW	视场	6°	7.5°	7.5°	7°	6.5°
	代/1,000M		426ft/1000Yds	426ft/1000Yds	450ft/1000Yds	370ft/1000Yds
	米/1,000M		131M/1000M	131M/1000M	137M/1000M	113M/1000M
CLOSE DISTANCE(M)	近焦距离	4	3	3	3	3
RELATIVE BRIGHTNESS	相对亮度	21.2	25	25	25	16
TWILIGHT INDEX	暗光指数					
DIOPTOR ADJUSTMENT	屈光调焦	±4	±5	±5	±5	±5
WATER PROOF	防水	NO	NO	NO	NO	NO
NITROGEN FILLED	氮气充氮	NO	NO	NO	NO	NO
DIMENSIONS OF PRODUCT	产品尺寸	185x52x120	165 × 53 × 125	170 × 56 × 150	180 × 60 × 150	205 × 60 × 170
NET WEIGHT(G)	产品净重	700	570	650	700	720
PICKING	包装	纸箱				

OEM 系列 **MOQ:500**

PICTRUE	图片				
MODLE	型号	OEM 8X40	OEM 7X50	OEM 10X50	OEM 12X50
MAGNIFICATION	倍数	8X	7X	10X	12X
EYEPIECE DIAMETER	目镜直径	23	23	23	19
EYEGLASS SYSTEM	目镜结构				
OBJECTIVE DIAMETER(MM)	物镜直径(MM)	40	50	50	50
FRONT LENS DIAMETER(MM)	前镜直径(MM)	52	58	58	58
PRISM	棱镜	BK7	BK7	BK7	BK7
FOCUS SYSTEM	调焦结构	PORRO	PORRO	PORRO	PORRO
LENS COATING	镜片镀膜	FMC	FMC	FMC	FMC
EXIT PUPIL DIAMETER	出瞳直径	5	7	5	4.2
EYE RELIEF	出瞳距离	23	20	20	18
FIELD OF VIEW	视场	7.5°	7°	6.5°	5°
	代/1,000Yds	426ft/1,000Yds	405ft/1,000Yds	378ft/1,000Yds	331ft/1,000Yds
	米/1,000M	131M/1,000M	123M/1,000M	113M/1,000M	101M/1,000M
CLOSE DISTANCE(M)	近焦距离	3	3	3	10
RELATIVE BRIGHTNESS	相对亮度	25	16.4	16	11.6
TWILIGHT INDEX	暗光指数	17.9	18.7	22.3	24.5
DIOPTOR ADJUSTMENT	屈光调焦	±4	±4	±4	±4
WATER PROOF	防水	NO	NO	NO	NO
NITROGEN FILLED	氮气充氮	NO	NO	NO	NO
DIMENSIONS OF PRODUCT	产品尺寸	135x60x187	179x62x190	179x63x190	179x63x190
NET WEIGHT(G)	产品净重	600	650	650	650
PICKING	包装	纸箱			